

POLOMERY OCHRANY PODĽA NF C 17-102:2011

ÚROVEŇ OCHRANY LPL I (r=20m)					
WAT Franklinplus	W10	W20	W30	W45	W60
ΔT [μsec]	10	20	30	45	60
h [m]			Rp [m]		
2	10	14	19	25	31
3	15	22	28	37	47
4	20	29	38	50	62
5	26	37	47	63	78
20 max	30	40	50	65	80

ÚROVEŇ OCHRANY LPL II (r=30m)					
WAT Franklinplus	W10	W20	W30	W45	W60
ΔT [μsec]	10	20	30	45	60
h [m]			Rp [m]		
2	12	17	21	28	34
3	18	26	32	42	51
4	25	34	43	56	69
5	31	43	54	70	86
20	38	49	59	74	89
30 max	40	50	60	75	90

ÚROVEŇ OCHRANY LPL III (r=45m)					
WAT Franklinplus	W10	W20	W30	W45	W60
ΔT [μsec]	10	20	30	45	60
h [m]			Rp [m]		
2	15	20	25	32	38
3	22	30	38	48	58
4	30	41	50	64	77
5	37	51	63	80	97
20	49	60	70	86	102
45 max	55	65	75	90	105

ÚROVEŇ OCHRANY LPL IV (r=60m)					
WAT Franklinplus	W10	W20	W30	W45	W60
ΔT [μsec]	10	20	30	45	60
h [m]			Rp [m]		
2	17	23	28	35	42
3	26	34	42	53	64
4	34	46	57	71	85
5	43	58	71	89	106
20	57	69	80	97	113
60 max	70	80	90	105	120