


nVent ERICO Ericore vodič bez koncoviek



- Kábel s nízkou indukčnosťou a nízkou impedanciou určený na minimalizáciu nárastu napätia v dôsledku bleskových impulzov
- Viacnásobné izolované vrstvy vodičov znižujú potenciál bočných výbojov
- Vyžaduje hornú a dolnú ukončovaciu sadu



Číslo dielu	Artikel číslo	Dĺžka L	Kapacitancia	Prierez	Priemer Ø	Impedancia	Inductancia	Rezistancia (R _{dc})	Rezistancia (R _{imp})	Napät'ová odolnosť hornej koncovky	Váha jednotky
ERICORE	701875	1 m	0,75 nF	50 mm ²	36 mm	12 Ω Max	37 nH	0,5 mΩ/m	6 mΩ/m	-	1,18 kg

Pokyny týkajúce sa maximálnych povolených dĺžok nájdete v technickej podpore nVent ERICO, alebo v inštalačnej príručke. Indukčnosť a kapacita sú na meter dĺžky.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.ericore.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.